

ROLLTEX Fire EI₂-60

Fire resistant roll up curtain



QUALITY SINCE 1967
Reliable Doors & Docks




Standard assembly on wall



Back view: Wall lintel closing.

Tunnel assembly (inside work gap)



Back view: Lacquered cover closing.

Hidden installation between walls



Back view: False ceiling and hidden guides.



Fire resistant roll up curtain without water irrigation, designed to control and compartmentalise fire. CE certified according to EN 16034/13241.



Key Benefits

- EI₂-60 fire resistance with integrity and thermal insulation.
- Automatic closing in case of fire alarm.
- Fail-safe descent during power failure.
- Protection for large openings up to 20 m width.
- Minimal architectural impact with concealed installation option.
- Multilayer insulated curtain for high fire performance.
- Integrated safety photocells for safe operation.



Max. Dimensions

20.000 mm × 10.000 mm.



System

- Multilayer fire-resistant curtain (15–20 mm thickness).
- Fiberglass fabric reinforced with stainless steel.
- Galvanized steel structure and guides.
- Motor with UPS backup system.
- Automatic closing during fire alarm.



Applications

Logistics centres, industrial buildings, shopping centres, airports, parking areas.

The information contained in this description is general and refers to the product. In no case is it binding or contractual. Portes Bisbal SL reserves the right to modify the specifications contained herein.